
BAGNODESIGN

EXPERTLY CRAFTED BATHROOMS

Installation Guide



MIRRORS
ILLUMINATED MIRRORS

A member of SANIPEXGROUP www.sanipexgroup.com

IMPORTANT PLEASE READ

Remove all packaging and check the product for missing parts or damage before starting installation.

Any alterations made to this product and fittings may infringe water regulations and invalidate the guarantee.

The Installation must comply with all Local/National Water Supply Authority Regulations/Byelaws and Building and Plumbing Regulations.

We strongly recommend that your product be installed by a reputable qualified trade's person.

General Installation:

To the Installer, please read and follow this instruction carefully, as the guarantee is only valid if the product is installed as directed.

Don't rush, read the instructions first and run through them before you begin. Keep fittings together to avoid loss. Do not over tighten screws or bolts.

If the product is covered with polyethylene protective film, do not remove until installation is complete to grant maximum protection. However, remove film where any two surfaces will be in permanent contact.

Please leave this installation manual with the end user once the product has been installed.

Product Aftercare:

We recommend cleaning with a soft damp cloth and mild soap solution. Do not use cream cleaners or cleaners containing bleach.

Do not scrub or scour.

Do not use abrasive cleaning agents.


Do not use solvent based cleaners.

Flectrical Connections

All electrical connections and alterations should be carried out by a qualified electrician and be in accordance with Part P regulations.

All BAGNODESIGN mirrors are IP rated to different standards and are suitable for installation in various zones. The diagram below illustrates this zonal concept and must be followed to ensure safe installation of electrical bathroom products.

The diagrams and information below are a guide to Bathroom Zones as referred to in IP ratings it is important to install an electrical product in the correct bathroom zone i.e. the zone referred to in the IP rating of the product. This is not an installation guide, and reference should be made to the latest edition of **IEE** wirings the Regulations qualified or а electrician.



Zone 0 is inside the bath or shower tray itself. Any appliance used in this zone must be rated at least IP67 which is total immersion proof.

Zone 1 is the area above the bath or shower tray to a height of 2.25m from the floor. In this zone a minimum rating of IP44 is required and products must also be protected by a 30mA residual current device (RCD) to protect the circuit. The electrical connection to the power supply for these products must be in Zones 2/3 of the bathroom in compliance with BS7671:2001 - IEE Wiring Regulations.

Zone 2 is an area stretching 0.6m outside the perimeter of the bath and to a height of 2.25m from the floor. In this zone an IP rating of at least IP44 is required. In addition, it is good practice to consider the area around a washbasin, within a 60cm radius of any tap to be considered as zone 2.

Function usage

"Switch sign"

1, Please choice below operation according to what product you buy:


A. Touch switch.

B, Touch switch holding to gradually dim.

C, Touch switch press-hold color change.

D, Tap-tap touch color change

E, The first short touch, turn on the light and demist pad; The second short touch, chang the color temperature. The third short touch, turn off the light and demist pad, when the light be turned on; the first holding touch; the brightness of the light can be changed from 100% to 10% or 10% to 100%, the second holding touch; the brightness of the light can be changed from 10% to 100% or 100% to 10%



Parts list





No this spare part if use the hardy holes installation Aluminum hanging bar

Installation tools (as shown below)



Flexible rule










Churn drill Leveling instrument Screwdriver Hammer


Warm tips,

- 1, Please do not use, if the product have any broken.
- 2, During operation, never put hard and sharp materials directly against the mirror surface. Otherwise, it may result in current leakage and even personal injury accident
- 3, Never forget to turn off the power switch in storm days. Otherwise, lightning may damage electric elements of the product.
- 4, During normal operation, never forcibly pull out the power plug to stop the product Otherwise, electric elements of the product may be damaged.
- 5. Please pull out the power plug if the product is not used for a long time.

A/ Hanging bar installation Manual (instruction for LED bathroom mirror)



B/ Hanging bar installation Manual (instruction for LED bathroom mirror)



BAGNODESIGN

EXPERTLY CRAFTED BATHROOMS				